



BBBG2.MH20839 Capacitors, Electrochemical - Component

[Page Bottom](#)

Capacitors, Electrochemical - Component

[See General Information for Capacitors, Electrochemical - Component](#)

TECATE INDUSTRIES INC

MH20839

7520 MISSION VALLEY RD


SAN DIEGO, CA 92108-4400 USA

Model	Single Capacitor	Capacitor Module	Stationary Use Only	Controlled Environment Temp Limits, °C*	Capacitance, F	Voltage
PB-2R5/040 may be followed by additional suffixes	X	—	—	—	4.0	2.5
PB-2R5/100 may be followed by additional suffixes	X	—	—	—	10.0	2.5
PBD-5R0/040 may be followed by additional suffixes	—	X	—	—	2.0	5.0
Series Type TPL, followed by -0.5 through 400, "/", 8 through 35, "X", 12 through 60. May be followed by additional suffixes.	X	—	—	—	0.5 - 400	2.7
Series Type TPLS, followed by -100 through 400, "/", 22 through 35, "X", 45 through 60. May be followed by additional suffixes.	X	—	—	—	100-400	2.7
Series Type PBL, followed by 0.25 through 17.0, "/", 5.4. May be followed by additional suffixes.	—	X	—	—	0.25-17.0	5.4
Series Type PBL, followed by 0.25 through 17.0, "/", 5.4. May be followed by additional suffixes.	—	X	—	—	0.25-17.0	5.4
Series Type PBL, followed by 0.25 through 15, "/", 5.4. May be followed by additional suffixes.	—	X	—	—	0.25-15	2.7 or 5.4#
Type PBL4 followed by 34 through 38, "/", 5.4. May be followed by additional suffixes	—	X	—	—	34-38	2.7 or 5.4#
Type PBL4 followed by 0.25 through 34, "/", 5.4. May be followed by additional suffixes.	—	X	—	—	0.25-34	5.4
17-0005-4483, 17-0011-4483, 17-0012-4483, 17-0013-4483, may be followed by additional suffixes A-K.	—	X	—	—	6.4	13.5
Models 17-0015-4483, 17-0016-4483, 17-0017-4483, 17-018-4483, may be followed by additional suffix letter A through Z.	—	X	—	—	6.4	13.5
17-0014-4483, may be followed by additional suffix letter A through Z.	—	X	—	—	2 to 2.2	13.5
17-0019-4483, may be followed by additional suffix letter A through Z.	—	X	—	—	6.8	13.5

17-0007-4483	—	X	—	—	2 to 2.2	13.5
17-0008-4483	—	X	—	—	12.8	13.5
17-0003-4483, may be followed by additional suffixes A-Z	—	X	—	—	5.0	10.0
TPL-0.33/5X11, TPL-0.33/6X9, TPL-0.5/6X9, TPL-1.2/6X15	X	—	—	—	0.33 to 100	2.7
TPLS-60/25X40	X	—	—	—	60 to 400	2.7
TPL-100/18X60F	X	—	—	—	0.33 to 100	2.7
17-0003-4840	—	X	—	—	10	2.7

* Only applicable to capacitors or capacitor modules for use in "stationary only" applications that are located in controlled environments.

Wiring configuration dependent; 5.4V for use of series connections, 2.7V for use of non-series connections.

Marking: Company name, model designation and the Recognized Component Mark .

Last Updated on 2014-08-07

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2014 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".